



Hitouch 4

CP17-72H

430-450W

MONO PERC

High Efficiency Module

20.70%

Maximum Efficiency

12 YEARS

Product Warranty



Higher Power Output

Higher module conversion efficiency benefit from bigger wafer and half-cell structure.

MBB technology enhances current collection with lower series resistance.



Excellent Temperature Coefficient

Lower operating temperature and temperature coefficient increases the power output



Long-Term Reliability

Module certified to withstand extreme wind (2400 Pascal) and snow loads (5400 Pascal).

Excellent anti-PID performance to guarantee a better sustainability in harsh environment.




Lower Hot Spot and Crack Risk

Reduce hot-spot risk with optimized electrical design and lower operating current.

Reduce crack risk by MBB solar cell design.

Power Warranty



12-year product warranty



25-year linear power output warranty

Insurance



Munich RE



太平洋保险 CPIC

Certificates



About Hanersun

Hanersun is a world leading solar module manufacturer and comprehensive energy solution provider. We provide customers with cutting edge solar modules, and services for the entire project life cycle.

Electrical Characteristics

Module Type	CP17-72H430W		CP17-72H435W		CP17-72H440W		CP17-72H445W		CP17-72H450W	
	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power (Pmax)	430	324	435	329	440	333	445	336	450	340
Maximum Power Voltage (Vmp)	40.30	38.00	40.50	38.20	40.70	38.40	40.80	38.50	41.00	38.70
Maximum Power Current (Imp)	10.67	8.54	10.74	8.61	10.82	8.68	10.90	8.73	10.98	8.80
Open-circuit Voltage (Voc)	48.80	46.10	49.00	46.30	49.20	46.40	49.40	46.60	49.60	46.80
Short-circuit Current (Isc)	11.24	9.05	11.31	9.11	11.39	9.17	11.46	9.23	11.53	9.28
Module Efficiency(%)	19.78%		20.01%		20.24%		20.47%		20.70%	

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5.
*Measuring tolerance: 0 ~ +5W

NMOT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

Mechanical Parameters

Solar Cells	Monocrystalline (166mm)
No. of Cells	144 [2 x (12 x 6)]
Module Dimensions	2094*1038*30mm
Weight	23.5kg
Glass	3.2mm, High Transmission, AR Coated Heat Strengthened Glass
Encapsulant Material	EVA/POE
Backsheet	White
Frame	Anodized Aluminium Alloy
J-Box	IP68
Output Cable	4.0mm ²
(Including Connector)	Length Portrait:300/300mm (can be customized)
Connector	MC4 Compatible

Temperature Ratings

NMOT (Nominal operating cell temperature)	45°C(±2°C)
Temperature Coefficient of Pmax	-0.330%/°C
Temperature Coefficient of Voc	-0.270%/°C
Temperature Coefficient of Isc	+0.050%/°C

(Do not connect Fuse in Combiner Box with two or more strings in parallel connection)


Packaging

Pcs per Pallet: 36
Pcs per 40' HC: 792


Operating Parameters

Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500V DC (IEC)
Maximum Series Fuse Rating	20A
Bifaciality	/


I-V Curves of PV Module (445W)




P-V Curves of PV Module (445W)



Dimensions (Unit: mm)



Front View



Long frame

Short frame

Back View